



SAFETY DATA SHEET

DPC No.1

Revision 0
Revision date 26-Feb-2009

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name DPC No.1
Company Wykamol Group Limited
Unit 3, Boran Court
Network 65 Business Park
Hapton, Burnley
Lancashire. BB11 5TH
sales@wykamol.com www.wykamol.com
Telephone 0845 400 6666
Emergency telephone number 0845 400 6666

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	1 - 10%	64742-88-7	265-191-7	Xn; R65
Iso-butanol (2-Methylpropan-1-ol)	1 - 10%	78-83-1	201-148-0	R10 Xi; R37/38-41 R67
Naphtha (petroleum), hydrotreated heavy	90 - 100%	64742-48-9	265-150-3	Xn; R65 R10-66

3. HAZARDS IDENTIFICATION

Main hazards Flammable Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.

Ingestion Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO2), dry chemical, foam.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Self-contained breathing apparatus. Wear protective clothing.

DPC No.1

Revision 0
Revision date 26-Feb-2009

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure limits**

Iso-butanol
(2-Methylpropan-1-ol)

WEL 8-hr limit ppm: 50
WEL 15 min limit ppm: 75

WEL 8-hr limit mg/m3: 154
WEL 15 min limit mg/m3: 231

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Clear.
Relative density	0.775 - 0.786

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information	There is no data available.
----------------------------------	-----------------------------

12. ECOLOGICAL INFORMATION

Ecotoxicity	There is no data available.
--------------------	-----------------------------

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Do NOT reuse empty containers.

DPC No.1Revision 0
Revision date 26-Feb-2009**14. TRANSPORT INFORMATION****ADR/RID**

UN 1993	Packing group III
Class 3	Hazard ID 33
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. ,


IMDG

UN 1993	Packing group III
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1993	Packing group III
Class 3	Subsidiary risk -
Packing Instruction 310 (Cargo)	Maximum quantity 220 L
Packing Instruction 309 (Passenger)	Maximum quantity 60 L

15. REGULATORY INFORMATION

Labelling	The product is classified in accordance with 67/548/EEC.
Symbols	Xn - Harmful 
Risk phrases	R10 - Flammable. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
Safety phrases	S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Text of risk phrases in Section 2	R10 - Flammable. R37/38 - Irritating to respiratory system and skin. R41 - Risk of serious damage to eyes. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.