

DRY ROT PAINT

Wykamol Dry Rot Paint is a specially formulated preservative emulsion coating for control of fungal growth and infection such as Dry Rot (**Serpula lacrymans**) on brickwork, masonry, render and timber.

Wykamol Dry Rot Paint is a high quality water based coating just over 1.0%w/w 3-Iodo-2-Propynyl-N-Butyl Carbamate.

It has been designed as a highly visible surface biocide and as a sterilising treatment against Dry rot and other decay fungi.

Wykamol Dry Rot Paint can also be used to protect timbers in proximity to a fungal outbreak or those used in reinstatement after an outbreak. It is a particularly useful treatment for coating the backs of joinery (skirtings/architraves) and concealed parts of window and door framework.

The main uses of Wykamol Dry Rot Paint are readily identified as:

- 1 A surface biocide and treatment against decay fungi on mineral and timber substrates.
- 2 A fungicidal coating for joist ends, apertures of windows and doors and exposed brickwork between floors.
- 3 A biocidal barrier under plaster and render.
- 4 A toxic barrier on the backs of joinery and concealed linings of door and window frames.

Special Features

- Low mammalian toxicity
- Low VOC (Volatile Organic Content) and quick drying
- High visible preservative emulsion with treatment readily identified
- Practically odourless
- Non flammable
- Equally effective on masonry and timber.

Issue Date : January 2009

Directions for use

1 Use a stiff brush to thoroughly clean all wall areas to at least 300 mm past the last identified extent of the fungal outbreak removing any surface growth or strands.

2 Further prepare the surfaces by removing all dirt, loose and flaking material.

3 Pay particular attention to minimise dust levels. Remove ALL dust and debris from site in accordance with good practice.

4 Ensure surfaces to be treated are free of efflorescence. Efflorescence can be removed using Wykamol Salt Neutraliser (see product TDS).

5 Thoroughly stir the **Wykamol Dry Rot Paint** before use.

6 Sterilise all exposed wall areas by applying two liberal coats of **Wykamol Dry Rot Paint** using a brush or roller, working well into all cracks, joints and defects.

7 Apply two coats to provide maximum protection with the second coat applied when first coat is touch dry. Allow to dry.

8 Apply one liberal coat **Wykamol Dry Rot Paint** to prepared (smooth) timber and allow to dry.

Apply two liberal coats **Wykamol Dry Rot Paint** to rough sawn (porous/rough) timber with the second coat when first coat is touch dry. Allow to dry.

9 Clean equipment and any spillages with water.

Coverage

2-8 square metres per litre depending on type and condition of substrate.

Available in 5 litre containers.

Health and Safety

The product is registered under the HSE (COPR 1986 Regulations for use as directed (HSE No. 6520). Refer to Safety Data Sheet (SDS) for the product.

Keep away from children.



Wykamol Group

Unit 3 Boran Court, Network 65 Business Park, Hapton, Burnley. BB11 5TH

t: +44 (0)845 400 6666 f: +44 (0)845 400 3333

www.wykamol.com e: sales@wykamol.com