

Technical Leaflet



■ BASF Group

Dr. Wolman GmbH • 76547 Sinzheim/Germany • Tel. +49 7221 / 800 0 • Fax +49 7221 / 800 290 • E-Mail info@wolman.de • Internet www.wolman.de



Wolmanit[®] ProColor yellow 2204

Yellow colour concentrate based on water soluble dyes

1. Usage

Type of product	Liquid concentrate based on water soluble dyes for the colouration of wood treated in a double vacuum process in combination with wood preservative solutions (e. g. Wolsit [®] KD products). As for all dyes, the UV- stability of Wolmanit [®] ProColor yellow 2204 is limited. The durability of the colour is depending on the time and intensity to UV light.
Field of application	Colouration of impregnated timber, especially structural timber (e. g. trusses, beams, laths etc.).

2. Product Specification

Density	approx. 1.09 g/cm ³ (at 20 °C)
pH value	approx. 3.5 – 4.5 (10% solution at 20 °C)
Labelling	 Xn – harmful  N – dangerous for the environment

3. Application

Solution strength	For double vacuum treatment, the typical concentration is 0.01 – 0.02 %. Thoroughly stirring and a colouration test on timber is recommended if the working solution is not used for a longer period of time.
Preparation of solution	A 0.01% concentration is equivalent to 1 kg of Wolmanit [®] ProColor yellow 2204 per 10000 litres of treatment solution. Wolmanit [®] ProColor yellow 2204 should be added along the complete length of the storage tank in order to achieve the best possible pre-distribution of the product. Afterwards the solution has to be stirred to achieve a homogeneous distribution.
Storage of impregnated timber	Right after treatment, the dyes could be washed off easily by rain. Therefore, the timber should be sheltered from rain during fixation.

4. Storage	
Storage	Minimum shelf-life in tightly closed container: 2 years. To be stored in original containers only. Keep out of reach of children.
Storage temperatures	Wolmanit® ProColor yellow 2204 should be kept at temperatures of +5 °C to +35 °C. Protect from frost.

5. General instructions	
Safety Precautions	<p>A material safety data sheet is available at the above address and to be used with this technical leaflet. Before use, read product instructions carefully.</p> <p>For preparation and use of treatment solutions, technical leaflet and material safety data sheet of the treatment chemical has also to be observed.</p> <p>For use by professionals only.</p> <p>Colour additives may negatively affect the impregnation success as well as corrosion. A suitable coating of the plant is generally recommended.</p> <p>The result of colouration may vary due to different timber surface conditions, e.g. roughness, pre-weathering, tight packing, use of stickers etc.</p> <p>Washed-out dye may stain masonry, cladding and seating furniture.</p> <p>Do not use eating and drinking bins for the product.</p> <p>When using the product, do not eat, drink or smoke.</p> <p>Keep out of reach of children.</p> <p>Do not store along with foodstuffs, beverages and fodder.</p> <p>Wear suitable protective equipment such as safety goggles and gloves.</p> <p>Wolmanit® ProColor yellow 2204 and its solutions may not leach into soil, canalisation and surface water.</p>

This information and all further technical advice are reflecting our present knowledge and experience based on internal tests with local raw materials with the purpose to inform about our products and applications. The information should not be construed as guaranteeing specific properties of products described or their suitability for a particular application, nor as providing complete instructions for use. The information implies no guarantee for product and shelf life properties, nor any liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights.

Application and usage of our products based on our technical advice is out of our control and sole responsibility of the user. The user is not released from the obligation to conduct careful inspection and testing of incoming goods in order to verify the suitability for the intended application.

For experimental products we do not guarantee for later commercial availability. In addition our general terms and conditions for sale are valid.