

# Technical Leaflet



■ BASF Group

Dr. Wolman GmbH · 76547 Sinzheim/Germany · Phone. ++49 7221 / 800 0 · Fax ++49 7221 / 800 290 · E-Mail info@wolman.de · Internet www.wolman.de

## Wolmanit<sup>®</sup> C&T Brown




Wolmanit<sup>®</sup> C&T Brown is a brush-on end-grain preservative for exterior use only.  
For the re-treatment of cross-cut or bored Wolmanit<sup>®</sup> CX pressure treated timber.

### 1. Usage

Field of Application	<p>The professional vacuum pressure treatment of timber with Wolmanit<sup>®</sup> CX treatment products leads to an efficient protection against wood destroying fungi and insects.</p> <p>In some cases, e.g. terrace decks or claddings, pressure treated timber needs to be cut to size, notched or bored.</p> <p>If pressure treated timber is further processed like explained, the end-grain should be re-treated with Wolmanit<sup>®</sup> C&amp;T Brown.</p> <p>Only for exterior use without ground or fresh water contact.</p>
Application Method	Apply by brush directly.
Wood Species	No restriction.

### 2. Product Specification

Form of Supply	<p>Wolmanit<sup>®</sup> C&amp;T Brown is a ready to use, waterbased, blue, liquid product based on Copper(II)-hydroxide-carbonate and Propiconazole.</p> <p>Depending on the number of coats, the product leads to a lighter or darker brownish appearance of the timber.</p>
Density	Approx. 1.0 g/cm <sup>3</sup> (at 20 °C)
pH Value	Approx. 9.8 (at 20 °C)
Labelling	 Xi - Irritant

### 3. Application

Preparation of Solution	Wolmanit® C&T Brown is ready to use and shall be applied undiluted.
Handling	Shake well before use. Brush on Wolmanit® C&T Brown in two saturated coats. Let the end-grain dry out well between the coats. Keep timber rain protected during fixation time of 48 hours. Keep timber away from ground or fresh water contact.  After completion of work and before meals, hands and exposed skin should be washed thoroughly with water or a suitable cleaning agent.
Cleaning of Equipment	Directly after usage with clean water. Remove as much product as possible away from the brush before cleaning with water. Do not pour away product or washings down the drain.
Disposal	Dispose of Wolmanit® C&T Brown by special means in accordance with local regulations e.g. suitable incineration.

### 4. Storage

Storage	Minimum shelf life 2 years in original sealed can. Shake well before use.
Temperatures	Wolmanit® C&T Brown should be kept at temperatures of +5 °C to +35 °C. Protect from frost.

### 5. General Instructions

Safety Precautions	A material safety data sheet is available at the contact details above. Read product information and labelling carefully before use.  Wear suitable protective equipment such as safety goggles and gloves.
Labelling	Irritating to eyes, respiratory system and skin.  Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  Contains Propiconazol. May cause an allergic reaction.  Keep out of reach of children. Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. In case of accident or if you feel unwell, seek medical advice (show the label if possible).

### 6. Note

The information submitted in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors of the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Use wood preservatives safely. Always read the label and product information before use.